



Description

Pro Matt Enamel reflects your taste for refined and opulent coating. It provides durable and non dazzling regal matt finish that is excellent resistant to moisture and stain. It is alkyd based paint that is dried by air and retains the original characteristics of excellent finish even after several washings. Available in colors that resonate with your definition of style and charisma.

Recommended For

Pro Matt Enamel is suitable for all interior surfaces including masonry walls, brickworks and wood substrates. Use proper primer system for longer life of coating.

Pro Matt Enamel

Features

- Excellent resistant to steam and moisture
- Excellent flow and coverage
- Washable and stain free
- Excellent resistant to abrasion
- Air drying with smooth matt finish
- High color fastness pigments

Limitations

- Drying time may vary depending on weather and drying conditions.
- Ensure the correct primer and/or sealers are used.

Product Information

Tint Bases: Pro Paints Standard Tinters.	<u>Vehicle type</u> Solvent based alkyd
Color Range: See appropriate shade card.	<u>Pigment type</u> Titanium dioxide
	<u>Volume solids</u> 46±2 %
	<u>Weight solids</u> 73±2 %
	<u>Specific gravity</u> 1.25±0.02
	<u>Viscosity</u> 565 ± 40 Sec @ F4 Cup
	<u>Flash point</u> 42 °C
	<u>PH</u> Not applicable
	<u>Application</u> Brush, Roller, Spray
	<u>Finish</u> Matt
	<u>Thinner</u> Mineral turpentine
	<u>Thinning</u> As per requirement, Max 25%
	<u>Dries by</u> Evaporation, Oxidation
	<u>Surface Dry</u> 2-3 Hours
	<u>Hard Dry</u> 24 hours
	<u>Recoat</u> 16 hours
	Drying and recoat times are temperature, humidity and film thickness dependent
	<u>Film thickness (dry)</u> 25-30 microns per coat
	<u>Coverage</u> 12-13m ² /liter/coat
	<u>Packing</u> 3.64 ltr, 0.91 ltr
	<u>Storage temperature</u> 4-30 °C
	<u>Color Range</u> See appropriate shade card.
Technical Help: Pro Paints technical department is always available to assist you in the correct use of our products.	

Surface Preparation and Application

Appropriate and good surface preparation significantly increases the top coat life and durability. Deploy skilled/experienced individuals for the application of paint. A few general instructions are given below:

New or Bare surfaces

Surface to be painted must be dry, clean and free from all contamination. Remove dirt, grease and waxy material. Scuff with suitable sand paper, dust off and apply Pro Red Oxide Primer or Pro Zinc Chromate Primer on all metal surfaces in order to prevent from rusting. Allow the surface to dry completely and apply 2 coats of Pro Matt Enamel. The recommended paint system for different system is given below:

Previously painted surfaces

Scrape off all the loosely adherent paint from the surface with an appropriate abrasive paper. Properly clean the substrate and apply Pro Red Oxide Primer or Pro Zinc Chromate Primer on all metal surfaces in order to prevent from rusting. Allow the surface to dry completely and apply 2 coats of Pro Matt Enamel. The recommended paint system for different systems is given below:

Recommended Paint System for METAL Substrates

Sequence	Recommended Product	No. of Coats
Primer	Pro Zinc Chromate Primer	1
Finish	Pro Matt Enamel	2-3

Recommended Paint System for WOOD Substrates

Sequence	Recommended Product	No. of Coats
Primer	Pro Zinc Chromate Primer	1
Finish	Pro Matt Enamel	2-3

Recommended Paint System for MASONRY Substrates

Sequence	Recommended Product	No. of Coats
Sealer	Pro Wall Primer Sealer	1
Putty/Filling	Pro Strong Wall Filling	1-2
Finish	Pro Matt Enamel	2-3

Health and Safety Notes

- When applying Paint, take appropriate eye wear protection.
- In case of eye contact with product, rinse with plenty of water for at least 10 minutes.
- Don't breathe spray mist or dust.
- Ensure proper ventilation when applying paint.
- If swallowed, it may cause serious damage.
- When empty, don't use its container for edible storage.
- Place out of reach of the children.
- Pregnant women are advised to avoid breathing of paint mist or spray.
- In case of any emergency, undergo medical supervision as soon as possible.

WARNING: Scrapping/sanding off previously painted surfaces may release lead dust or fumes. Lead is highly toxic; take protective measures thoroughly when rubbing off the old surfaces.

The information provided in this data sheet is accurate and authentic to the best of our knowledge and based on standard tests. However results may vary due to possible variations in field conditions and application procedures.

Pro Paints (Pvt.) Ltd.